

Duct Air Leakage Tester with Built-in Printer

G9800 Series - G9803



Standard Accessories

- 1 x Duct Air Leakage Tester
- 1 x Flow Grid
- 1 x Low Flow Nozzle
- 6 x Silicone Tube (white)
- 1 x Duct Connection Hose
- 1 x Power Cord
- 1 x Container
- 6 x Silicon Tube (blue)
- 6 x Silicon Tube (red)
- 1 x Calibration Certificate
- 1 x Instruction Manual

Specifications		Best Accuracy
Air Flow	Range	(Matrix): 36~640 m ³ /h (Nozzle): 4~36 m ³ /h
	Accuracy	The reading is $\pm 2.5\% \pm 0.1$ m ³ /h
	Resolution	0.01 m ³ /h
Static Pressure	Range	± 2500 Pa
	Accuracy	Readings are 1% ± 1 Pa
	Resolution	0.1 Pa
Temperature	Range	0~60°C
	Accuracy	± 0.5 °C
	Resolution	0.1°C
Atmospheric Pressure	Range	70~130k Pa
	Accuracy	Readings are $\pm 2\%$
	Resolution	0.1k Pa
Power Supply	G9803-0E	100-120V, 1 Phase, 50/60Hz, 16A
	G9803-1E	200-240V, 1 Phase, 50/60Hz, 10A
Weight		Net weight approximately 72 Kg
Dimensions (WxDxH)		98 x 63 x 63 cm
Data Logging		Up to 1000 measurements