

## KH 18 LTX BL 24 Q (601714800) Cordless combination hammer 18V 2x4Ah LiHD; Charger ASC 55; metaBOX 165 L; with Metabo Quick change chuck

Order no. 601714800  
EAN 4061792218574



Product may differ from image



- Extremely light and compact cordless hammer with integrated extraction interface
- Maximum drill performance, efficiency and service life thanks to brushless technology and high-performance hammer action
- Dust-free drilling with compact dust extraction ISA 24 (accessory)
- Combination hammer with 3 functions: hammer drilling, drilling and chiselling
- Metabo VibraTech (MVT): integrated damping system to reduce vibrations in order to protect the user's health
- Metabo Quick: quick change between SDS Plus hammer chuck and keyless chuck for many different applications
- Vario-Tacho-Constamatic (VTC)-Full Wave Electronics for work with materials requiring customised speeds, which remain constant under load
- Electronic soft start for precise spot-drilling
- Double safety when the drill bit jams: No kick-back thanks to the mechanic decoupling plus ultra-fast sensor-controlled shutdown
- LED work light for optimum view of the drilling site
- Many brands, one battery pack system: This product can be combined with all 18V battery packs and chargers of the CAS brands: [www.cordless-alliance-systems.com](http://www.cordless-alliance-systems.com)

## Technical data

### Characteristics

|                                     |                  |
|-------------------------------------|------------------|
| Type of battery pack                | LiHD             |
| Battery voltage                     | 18 V             |
| Battery pack capacity               | 2 x 4 Ah         |
| Max. single blow energy (EPTA)      | 2.2 J            |
| Maximum impact rate                 | 4750 bpm         |
| Drill-Ø concrete with hammer drills | 24 mm / 1 "      |
| Drill-Ø masonry with core bits      | 82 mm / 3 7/32 " |
| Drill Ø steel                       | 13 mm / 1/2 "    |
| Drill-Ø soft wood                   | 30 mm / 1 3/16 " |
| No-load speed                       | 0 - 1280 rpm     |
| Bit retainer                        | SDS-plus         |
| Weight without battery pack         | 3 kg / 6.61 lbs  |

### Vibration

|                              |                       |
|------------------------------|-----------------------|
| Hammer drilling concrete     | 13.4 m/s <sup>2</sup> |
| Uncertainty of measurement K | 1.5 m/s <sup>2</sup>  |
| Chiseling                    | 9.1 m/s <sup>2</sup>  |
| Uncertainty of measurement K | 1.5 m/s <sup>2</sup>  |

### Noise emission

|                              |           |
|------------------------------|-----------|
| Sound pressure level         | 90 dB(A)  |
| Sound power level (LwA)      | 101 dB(A) |
| Uncertainty of measurement K | 3 dB(A)   |

## Scope of delivery

Hammer chuck for tools with SDS-plus shank end  
 Drilling depth guide  
 2 LiHD Battery packs (18 V/4.0 Ah)  
 Charger ASC 55 "AIR COOLED"  
 metaBOX 165 L  
 Keyless chuck for tools with cylindrical shank  
 rubber-coated side handle